

## AXIS T8414 Installation Display

Handheld device to make camera adjustments a snap.



- > For image settings, viewing angle and focus
- > User-friendly
- > Snapshots
- > Video clip recording and playback

AXIS T8414 Installation Display is a battery-powered handheld device that greatly simplifies the field installation of Axis network video cameras and analog cameras.

AXIS T8414 connects directly to a camera and displays live video, which simplifies the setting of the camera's viewing angle and focus. In field installations the use of a laptop may be awkward when installers work from sky lifts or ladders. With its simple handheld design, AXIS T8414 can be used in any installation site.

An Axis network video camera with built-in Power over Ethernet support can be powered directly by AXIS T8414, which gives greater flexibility in field installations. Power is delivered from the device's battery or through Power over Ethernet by-pass from an alternative power source.

The touchscreen simplifies image setting adjustments, PTZ control, video clip recordings and playback of clips previously downloaded or recorded with AXIS T8414. For zoom functionality in the live video, only press the buttons on the unit. Snapshots and video clips can be saved to internal memory, or to a connected MicroSD card or USB device.

AXIS T8414 connects directly to the network video camera using the Ethernet port or BNC port when installing analog cameras. AXIS T8414 can also be connected to a network and search for Axis network video products.




## Technical Specifications – AXIS T8414 Installation Display

Display	
<b>Color LCD field display</b>	3.5 in, Automatic aspect ratio adjustment
<b>Resolutions</b>	320x240
Video	
<b>Image settings</b>	Autosensing, Brightness, Color level, Contrast
<b>Pan/Tilt/Zoom</b>	PTZ control
<b>Video streaming</b>	Support for up to 5 MP cameras
Network	
<b>IP setting</b>	Static IP adress, DHCP
System integration	
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX®; specifications at <a href="http://www.axis.com">www.axis.com</a>
General	
<b>Casing</b>	ABS plastic Color: Dark blue
<b>Memory</b>	128 MB RAM, (16 MB available for snapshot) Local storage: MicroSD card up to 32 GB (card not included)
<b>Installation aids</b>	Focus assistant, Video clip recording and playback, Snapshot File size max. 24 MB, H.264, MPEG, MAC address detection
<b>Measurements</b>	Bandwidth calculation, Cable test, PoE measurement
<b>Power</b>	12 V DC
<b>Battery</b>	BP-915 (7.4 V 2200 mAh) 80% capacity after 300 charge cycles Charge time 3.5 hours Operation time 3 hours with PoE off, 2 hours with PoE on

<b>Connectors</b>	BNC Video in RJ45 CAT-5 USB 2.0 PoE 10BASE-T/100BASE-TX PoE IEEE 802.3af Class 2, IEEE 802.3af Class 3 and IEEE 802.3at require mains power connection
<b>Operating conditions</b>	0 °C to 50 °C (30 °F to 122 °F) Humidity 20–80% RH (non-condensing)
<b>Approvals</b>	CE Class B, FCC Part 15 Subpart B Class B, ICES-003, AS/NZS CISPR 22, EN 55022, EN 61000-3-2, EN 61000-3-3, EN 50130-4, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-11, CISPR PUB 22
<b>Dimensions</b>	170 x 99 x 38 mm (6.7 x 3.9 x 1.5 in)
<b>Weight</b>	450 g (0.99 lb)
<b>Included accessories</b>	Soft carrying case with sunshield, Protective rubber sleeve equipped with a stylus pen and a spare for touch screen, Terminal block for CAT-5 cable test, Ethernet cable, BNC cable, Car charger 12 V DC, Power supply, Installation Guide
<b>Warranty</b>	Axis 1-year warranty, <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

More information is available at [www.axis.com](http://www.axis.com)

### Dimensions



### Compatible products

1. Axis network cameras
2. Axis video encoders

